

## **TITLE OF THE INVENTION**

Multipurpose Storage Device

## **BACKGROUND OF THE INVENTION**

### **1. Field of the Invention**

The present invention relates generally to storage device that is designed and configured to preferably maintain, house and protect any type or model of conventional ladder and more particularly to a multipurpose storage device that includes a universal mounting means for enabling secured attachment to any conventional object, such as the outer edge of a truck's bed, frame mounts generally secured to truck's beds, or the like.

### **2. Description of the Prior Art**

The use of a ladder is essential in many types of work. However, due to the bulky and cumbersome size of many ladders, devices have been developed to provide storage for the ladder during transportation. One such device provides for ladder storage via a rack mounted on one side of the truck bed. The ladder is then transported on the rack, thereby providing a convenient and efficient method of transporting the ladder. The prior art does not support an adjustable ladder cover compatible with all ladder styles and sizes that provides for additional storage compartments with a means for locking. Therefore, it is not surprising that numerous attempts have been made to fulfill the disadvantages of the present ladder covers.

One such example is seen in U.S. Patent Number 4,726,446 issued to Perbix wherein disclosed is a protection cover for ladder to reduce ladder slip and electrical shock. This device is intended for use when the ladder is at full extension to minimize

damage to an upright support, and minimize electrical shock by electrically insulating the ladder from the support. The cover is provided with resilient electrical non-conductive pads, which minimize movement of the upper end of the ladder. In addition, the cover is provided with a pocket structure for storage of tools and the like.

Accordingly, it is seen that there is a need for a storage device that is designed and configured to be utilized for protecting and housing any sized object and preferably one that is ideally suited for any model or sized conventional ladder. This device should include a universal attaching element for enabling attachment to any conventional surface, such as the bed of a truck, frame mounts, or the like. In addition, the device should include various compartments for enabling other objects, such as tools or the like to be stored therein. Inherently providing a device that will provide for weatherproofing and safekeeping of any desired object.

As will be seen, the present invention achieves its intended purposes, objectives and advantages by accomplishing the needs as identified above, through a new, useful and unobvious combination of component elements. The present invention is a device is convenient and one that is simple to use, with the utilization of a minimum number of functioning parts, at a reasonable cost to manufacture, assemble, test and by employing only readily available material.

## **SUMMARY OF THE INVENTION**

The present invention is multipurpose storage device that is designed and configured to house a plurality of objects, regards of their size and shape. Preferably, one object that is to be stored is a ladder. This will provide for the device of the present invention to be adapted to maintain, house and protect any conventional ladder, regardless of its size and/or shape. The present invention is ideally suited for transportation purposed, providing a device that will enable an individual to successful transport desired items in the storage device of the present invention, with the fear of harm, theft or the like from occurring therewith. Thereby providing a device that will inherently increase the shelf life of the particularly stored object.

In order to provide for such a multi-purpose storage device, the present invention comprises a box assembly. In the simplified embodiment, the box assembly includes a box structure having a upper wall, lower wall, side walls, a front and rear wall, which, together form the substantially box configuration.

Located on the front and/or rear wall is a door that when opened exposes the interior area of the storage device of the present invention. A lock or the like is secured thereto for enabling this front and/or rear wall to be lock and thus prevent theft from occurring. This will provide for a storage device that is elongated and is sized so as to accommodate any conventional ladder, such as a seven foot ladder, ten foot ladder, twelve foot ladder or the like.

Extending outwardly from the lower wall is a flange member. This provides for the flange member to be located to each side wall. Hence providing for two flanges, which innately form a lip. Extending through this lip is a plurality of apertures. The

apertures are adapted to receive conventional attaching elements such as screws or the like. Consequently providing for the flanges, apertures and attaching elements to inherently form the attaching device for enabling the present invention to be attached to any desired surface, such as the upper edge of a truck's bed, a frame secured on a truck or the like.

To decrease wind resistance, such as when the present invention is attached to a truck or the like, the front wall is angularly attached. This arrangement will provide for front wall to be angularly disposed from the top wall to the bottom wall.

Other features can be added to enhance the box of the present invention. One feature that can be added is the use of at least one additional compartment or container. This at least one compartment or container can be located on above, below or on the side of the box assembly. Access to the compartments or container will occur via a door that can be lockable. The doors can be located on any accessible wall.

When the compartment or container is located on the side(s) of the box assembly, then the compartment will include the flange having the plurality of apertures for inherently providing for the final product to include outer side walls having a lip secured thereto.

Alternative, a plurality of compartments can be provided so as to provide for each compartment to be removably secured to a desired wall of the box assembly. In this arrangement each container will include a removably attaching device that corresponds to an attaching device located on the upper wall, side walls and/or lower wall. The attaching device can be any conventional feature.

To utilize the present invention, if provided, the user the various compartments to the box assembly, as desired by the individual. Once located thereon, the present invention is secured to the desired surface, such as the bed of a truck or the like. Once secured, the various access means of the box assembly as well as the compartments are open to render access therein. The user can store and/or retrieve any desired item. After use, each compartment is locked, including the box assembly, to provide for the items to be safe, dry and thief free.

Accordingly, it is an object of the present invention to provide for a multipurpose storage device which will overcome the deficiencies, shortcomings and drawbacks of prior store devices and methods thereof, especially those related to the storage of conventional ladders.

Another object of the present invention is to provide for a multi-purpose storage device which features the capability of storing any style or size conventional ladder in a weatherproof environment while still providing for the stored ladder to be easily accessed, retrievable and storable.

Yet another object of the present invention is an multipurpose storage device that includes a multiplicity of storage compartment that will efficiently store, maintain and protect any desired items, ultimately providing a device that enables the use to store and categorize their items via the compartment, innately providing a storage and organization element.

A further object of the present invention is to provide for a multi-purpose storage device that should enable the user to adequately and efficiently store tools and the like in individual weatherproof compartments separate from the ladder, which can be locked for

controlled access. Thus, placement and retrieval of tools and the like can take place easily and quickly without the need for the user to dislodge or access the ladder.

Still a further object of the present invention is to provide for a multi-purpose storage device that meets the needs of being simple in design and relatively inexpensive to manufacture, so as to enable any homeowner, contractor or the like, from owning and utilizing such an convenient and adequate storage device.

Another object of the present invention to be specifically enumerated herein, is to provide a multipurpose storage device in accordance with the preceding objects and which will conform to conventional forms of manufacture, be of simple of construction and easy to use so as to provide for a device that would be economically feasible, long lasting and relatively trouble free in operation.

Although there exists several types of storage device none of the previous devices disclose a separate compartment for storing and maintaining a conventional ladder. The present invention meets the requirements of the simplified design, compact size, low initial cost, low operating cost, ease of installation and maintainability, and minimal amount of training to successfully employ the invention.

The foregoing has outlined some of the more pertinent objects of the invention. These objects should be construed features and applications of the intended invention. Many other beneficial results can be obtained by applying the disclosed invention in a different manner or modifying the invention within the scope of the disclosure. Accordingly, a fuller understanding of the invention may be had by referring to the detailed description of the preferred embodiments in addition to the scope of the invention defined by the claims taken in conjunction with the accompanying drawings.

1. The first part of the document discusses the importance of maintaining accurate records of all transactions and activities. It emphasizes the need for transparency and accountability in financial reporting.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

**Figure 1a** is a perspective view of the box assembly of the multi-purpose storage device of the present invention.

**Figure 1b** is a side view of the box assembly of the multi-purpose storage device of the present invention.

**Figure 1c** is a top view of the box assembly of the multi-purpose storage device of the present invention.

**Figure 2** is perspective view of a pair of box assemblies in a stacked position.

**Figure 3a** is a perspective view illustrating an alternative embodiment of the multi-purpose storage device of the present invention including a plurality of compartments attached to the box assembly.

**Figure 3b** is a side view illustrating an alternative embodiment of the multi-purpose storage device of the present invention including a plurality of compartments attached to the box assembly.



**Figure 3c** is a side view illustrating an alternative embodiment of the multi-purpose storage device of the present invention including a plurality of compartments attached to the box assembly.

**Figure 4a and Figure 4b** are perspective views illustrating an alternative arrangement for the compartment(s) used with the box assembly of the multi-purpose storage device of the present invention.

**Figure 5** is a perspective view illustrating an alternative embodiment of the multi-purpose storage device of the present invention including a plurality of compartments attached to the side of the box assembly and the compartments including a flange secured thereto.

**Figure 6a** is a perspective view of the box assembly of the present invention illustrating an example of an attaching device that can be used to removably receive a compartment.

**Figure 6b** is a perspective view of a compartment of the present invention illustrating an example of an attaching device that can be used to removably attach the compartment to the box assembly.

Similar reference numerals refer to similar parts throughout the several views of the drawings.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

With reference to the drawings, in particular to **figures 1-6b** thereof, the present invention, a multi-purpose storage, denoted by reference numeral **10** will be described. Shown is a multi-purpose storage device apparatus **10** that is designed and configured to receive and store a conventional ladder, tools, guns, fishing poles or any elongated object. The present invention is ideally suited for attachment to a vehicle, such a truck or the like, thereby providing an assembly that is versatile and one that can be utilized and enjoyed by hunters, contractors, home owners or the like, for adequately and efficiently storing, maintaining and protecting the items housed therein. Hence the present invention will be attached to a vehicle and enabled the user to transport items easily, conveniently and efficiently.

In order to provide for such a device, the present invention **10**, as seen in **figures 1a-1c** includes a box assembly **12** having an upper wall **14a**, lower wall **14b**, side walls **14c**, front wall **14d** and rear wall **14e**. Together, the walls form a box assembly **12** that includes an interior area that will receive and maintain a ladder. Access to the interior area occurs via a door **16** that can be locate on either the front wall or rear wall **14e** (as illustrated). The wall can constitute as a door, or optional, as illustrated, a separate door can be utilized. For aiding in the use of the door, a handle **18** can be located thereon. For preventing thief, a conventional lock or the like can be attached thereto.

Extending outwardly from the outer edges of the lower wall **14b** is a flange member **20**. This provides for the flange member **20** to be located to each side wall of the box assembly **12** so as to provide for the flange **20** to be parallel to each side wall. Hence

providing for two flanges, which innately form a lip. Extending through this lip is a plurality of apertures 22. The apertures 22 are adapted to receive conventional attaching elements such as screws or the like. Consequently providing for the flanges 20, apertures 22 and attaching elements to inherently form the attaching device for enabling the present invention to be attached to any desired surface, such as the upper edge of a truck's bed, a frame secured on a truck or the like.

To decrease wind resistance, such as when the present invention is attached to a truck or the like, and the vehicle is in motion, the front wall 14d is angularly attached. This arrangement will provide for front wall to be angularly disposed from the top wall to the bottom wall.

It is noted that this present invention can accommodate any conventional ladder and/or elongated object. If it is desirable to provide for a snug fit of the stored item, foam can be inserted therein. For example, if a ladder is stored therein and the ladder is seven feet in length, and the storage area is ten feet in length, then foam or other durable and rigid material, can be inserted therein for preventing movement of the stored item.

For those who have a multiple amount of ladders or elongated items, a pair of box assemblies 12 of the present invention, as seen in **Figure 2** can be stacked and secured to for intrinsically providing a multiple of units. To provide for such a configuration, the bottom wall of each unit is placed in contact with one another. The apertures 22 of the flanges 20 are aligned. Once aligned, screws or the like are inserted therein for enabling the units to be secured to each other. Thereby rendering an increase in storage capability. Alternatively, these apertures can be aligned to apertures located on the edge of the bed of a truck. The securing device, such as a screw, can extend from the aligned apertures 22 of

the flange into the aperture located in the truck for rendering the stacked units to be secured thereto.

Other features can be added to enhance the storage device **10** of the present invention. One feature that can be added is the use of at least one additional compartment or container **24** to the box assembly **12**. As seen in **figures 3a-3b**, the compartment(s) are secured to the lower wall **14b** of the box assembly **12**. This will provide for a device having a separate storage facility for the elongated object and separate compartments for other objects, such as tools, gear or the like. As shown, each compartment includes access means, such as a door **26** and handling capability, such as the use of a handle **28**. Each compartment can include a conventional lock secured thereto. The access means can be located on any accessible wall of the particular compartment. Thus, providing for the door to be accessible via a side wall (as shown), a top wall (see **figure 4a**), front wall, rear wall (see **figure 4b**), or bottom wall.

As seen in **figures 3a-3b**, the compartments are non-obtrusive in regards to the flange **20**, thereby providing for the flange to be free of obstruction and thus enable attachment to commence as discussed above. In addition, the compartment(s) can partially extend the length of the box assembly (see **figure 3b**) or optionally, can extend substantially the entire length of the box assembly (see **figure 3c**).

Alternatively, as seen in **figures 4a and 4b**, the at least one compartment **24** can be located above the box assembly **12**, thereby providing for the at least one compartment **24** to be secured to the upper wall. This arrangement will still provide access to the flange and prevent obstruction from the plurality of apertures.

The compartment(s) **24** can be secured to the side wall(s) of the box assembly **12**, as shown in **figure 5**. In this configuration, the compartment(s) that are secured to the side wall would include is at least one compartment or container can be located on above, below or on the side of the box assembly.

It is noted that at least two compartments can be utilized and the at least two compartments can be secured to any two separate walls (see **figure 5**). For example compartments can be secured to both the upper wall and lower wall. Alternatively, compartments can be located on the upper wall and at least one side wall.

When the compartment or container is located on the side(s) of the box assembly, as shown in **figure 5**, then the side compartment(s) will include the flange **20** having the plurality of apertures **22** for inherently providing for the final product to include outer side walls having a lip secured thereto.

Alternatively, a plurality of compartments can be provided so as to provide for each compartment to be removably secured to a desired wall of the box assembly **12**. As seen in **figures 6a and 6b**, in this arrangement each container **24** will include a removably attaching device **30a** that corresponds to an attaching device **30b** located on the upper wall, side walls and/or lower wall. The attaching device **30a** and **30b** can be any conventional feature. As seen, the attaching device **30b** for the box assembly **12** includes a projection **32** having a T-shape. As seen, the upper wall, bottom wall and side walls each include the projection **32**. This projection **32** is designed and configured to slide into channel **34** of the compartment **24**. As seen in **figure 6b**, the channel has an inverted T-shape that will correspond to the projection **32**. This will provide for the container to slide

onto the projection of the box assembly **12**. As seen, the upper wall, bottom wall and side walls each include the channel.

It is noted that if the container is to be located on the side walls, as least two oppositely located apertures must be accessible in order to enable the present invention to be attached to a desired surface. Due to the varying sizes of the container, the user can customized the device as deemed necessary.

In order to utilize the present invention, such as the embodiment illustrated in **figures 1a-1c**, the user secures the box assembly to the desired surface, such as the edge of the bed of a truck. The front wall or angled wall should face the front of the vehicle. Once secured, the access is used to provide access to the interior. The desired item to be stored therein, such as a ladder is placed therein. If a snug fit is desire, foam or the like is place therein for obtaining the desire fit. When located therein, the access is closed and if provided, locked.

In order to utilize the present invention, such as the embodiments illustrated in **figures 3a-5**, the user secures the device to the desire surface via the apertures located on the flange. The items desired to be stored are placed in their respective container. When located therein, the access of each compartment is closed and if provided locked.

In order to utilize the present invention, such as the embodiments illustrated in **figures 6a and 6b**, the user places the desired compartments at the desired located on the storage box **12**. Once located thereon, the device is secured to the desired surge via the use of the securing devices inserted into the apertures located in the flange. When located therein, the access is closed and if provided locked.

While the invention has been particularly shown and described with reference to an embodiment thereof, it will be understood by those skilled in the art that various changes in form and detail may be made without departing from the spirit and scope of the invention.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000